



2 Port USB KM Switch

No.: 32165

Switches Mouse and Keyboard between 2 computers

Description

- Controls two PCs using a single keyboard & mouse across two monitors
- Switch via software or keyboard hot keys
- Unique software allows for switching computers by simply sweeping a mouse from one screen to the other
- Integrated cables for quick, hassle-free installation
- 2 year warranty

A KM switch allows an operator to conveniently control and manage multiple devices, such as PCs and servers, from a single keyboard and mouse console.

The Lindy 2 Port USB KM Switch is a compact solution for providing control over two PCs with independent displays from a single keyboard & mouse. With integrated cables, this switch can be easily connected directly to the system, with no need to purchase additional cables, saving time and money on the installation.

The KM Switch can be managed with hotkey switching under every OS without any restrictions while a unique software provides simple switching between computers by sweeping a mouse across screens under Windows and Mac OS from 10.8.3 to Mac OS 10.14.

The KM Switch can be used with standard wired keyboard & mouse, wireless devices may not be recognized.

Simple to set-up and compatible with a wide range of Lindy USB Extenders, this solution is ideal for small education and business environments or for helping make the most of IT equipment in the home.

Please note: Software control is not currently compatible with devices supporting Linux and macOS 10.15. This is due to an incompatibility between macOS 10.15 and 32-bit software.

Technical details

Specifications

- USB Standard: USB 2.0
- Supported Bandwidth: 480 Mbps
- Chipset: KM0077
- Compatibility: USB Type A equipped computers
- Power Delivery: -
- Special Features: Switching via hotkeys, mouse cursor or software

Connectors

- Inputs: 2 x USB Type A (Male)
- Outputs: 2 x USB Type A (Female)
- Power: Bus-powered

Physical Properties

- Dimensions WxDxH: 105x50x20mm (4.13x1.97x0.79in)
- (Fixed) Cable Length: 1.1m (3.61ft)
- Housing Material: Plastic
- Net Weight: 0.073kg (0.16lb)
- Operating Temperature: -10°C - 50°C (14°F - 122°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 0 - 90% RH (non-condensing)
- Power Requirements: -
- Colour: Black

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 160x160x25mm (6.3x6.3x0.98in)
- Gross Weight: 0.117kg (0.26lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- KM Switch
- CD with Software
- Hook and Loop Self Adhesive Tape
- Lindy Manual

Purchasing information

- No.: 32165
- EAN: 4002888321655