



## 70m Cat.6 HDMI 18G, IR & RS-232 HDBaseT Extender with PoC, Transmitter

No.: 38213

Extend HDMI resolutions up to 70m via HDBaseT

### Description

- Distributes HDMI resolutions up to 70m over Cat.6 network cable via HDBaseT technology
- Supports HDMI 18G resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- RS-232 and CEC pass-through and bi-directional IR for simple control
- Supports PoC (Power over cable), requiring a power supply connection from only one side of the installation
- 2 year warranty

The Lindy C6 HDBaseT HDMI 18G & IR Extender, Transmitter is one part of a high performance, reliable solution for extending HDMI signals over long distances via Cat.6 network cable.

By combining this transmitter unit with a compatible Lindy HDBaseT receiver, this solution ensures reliable transmission up to 70m.

The following distance and resolution combinations are possible when using high quality Cat.6 U/UTP or F/UTP cable:

70m: 1920x1080@60Hz 4:4:4 8bit

40m: 3840x2160@60Hz 4:4:4 8bit / 4:2:2 12bit

Supporting resolutions up to 4K Ultra HD, video can be viewed in stunning clarity, while additional support for HDR (High Dynamic Range) allows content to be displayed with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut. This provides a reliable solution for creating eye-catching digital signage in retail, immersive displays at events or engaging setups in larger conference rooms or lectures halls.

PoC (Power over Cable) functionality provides additional flexibility. This allows power to be supplied alongside data through Cat.6 network cable in a point to point connection between the transmitter and receiver, meaning only a single power supply is required at the transmitter unit. Ideal when power outlets are limited at the receiver end of the installation.

Featuring bi-directional IR ports at both sides of the setup, the source equipment can be easily controlled from the display side, and the display can also be controlled from the HDMI source side. Combined with CEC control, which allows commands from one main remote, this extension system allows for complete and simple control for the user.

HDBaset is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance.

## Technical details

### Specifications

- AV Interface: HDMI
- Interface Standard: 2.0
- Supported Bandwidth: 18Gbps
- Maximum Distance: 70m (229.66ft)
- Maximum Resolution: 3840x2160@60Hz 4:4:4 8bit / 4:2:2 12bit
- HDCP Support: 2.2
- EDID Pass Through: Pass-through
- Supported Audio: Pass-through
- Separate Audio Ports: -
- IR Support: 30-60kHz
- CEC Support: Pass-through
- Serial Interface: RS-232 Pass-through
- Transmission Protocol: HDBaseT
- Transmission Medium: Cat.6
- Laser Class (only for Fibre): -
- Wavelength (only for Fibre): -
- Chipset: VS010
- Special Features:
  - Bi-directional IR
  - PoC (Power over Cat.6)

### Connectors

- Transmitter Input: HDMI Type A (Female), IR (Female)
- Transmitter Output: RJ-45 (Female), IR (Female)
- Receiver Input: -
- Receiver Output: -
- Bi-directional Ports: IR (Female)
- Power: 5.5/2.1mm

### Physical Properties

- Dimensions (approx.) WxDxH: 90x157x20mm (3.54x6.18x0.79in)
- Housing Material: Metal
- Net Weight: 0.345kg (0.76lb)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 20-90% RH (non-condensing)
- Power Requirements: 24VDC 1A
- Colour: Black

### Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 220x70x130mm (8.66x2.76x5.12in)
- Gross Weight: 0.847kg (1.87lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH & California Proposition 65

### Package Content

- HDMI Transmitter
- Multi-country Power Supply (UK, EU, US & AUS)
- IR Emitter Cable
- IR Receiver cable
- Lindy Manual

### Purchasing Information

- No.: 38213
- EAN: 4002888382137